

between the DC input and the AC output network.



# GATEWAY BDG-256P3



#### **COMMUNICATIONS INTERFACE**

Communication with Micro Inverter	AC Power Line Communication
Communication with RSD	DC Power Line Communication
Ethernet	10/100 auto-sensing, auto-negotiation
USB	USB 2.0 interface, auto-sensing, auto-negotiation
Monitoring capacity	255 micro inverters or RSD

### **HUMAN INTERFACE**

Display	7-in LCD touch screen
---------	-----------------------

## **POWER REQUIREMENTS**

AC inlet	Three-phase 208Vac, 380Vac, 50/60 Hz
Power consumption	8 watts maximum

### **MECHANICAL DATA**

Dimensions (W x H x D)	7.83" x 6.34" x 1.81" (199 mm x 161 mm x 46 mm)
Weight	5.29 oz (150g)
Ambient temperature range	-40°C to +55°C (-40° to 131°F)
Cooling	Natural convection - no fans
Enclosure environmental rating	Indoor - NEMA1

## **FEATURES**

UL 60950-1 2 <sup>∞</sup> Edition Rev Dec 19, 2011 CSA C22.2 2 <sup>∞</sup> Edition Rev Dec 19, 2011 FCC Part 15 Class B AS/NZS 60950.1:2011 Inc A1 AS/NZS CISPR 22: 2009+A1:2010 EN 60950-1:2006+A11:2009+A1:2010+A12:2011 EN 55022:2010 EN 61000-3-2:2006+A1:2009+A2:2009 EN 61000-3-3:2008 EN 55024:2010 EMC Directive 2004/108/EC	Standard warranty term	1 Year
	Compliance	CSA C22.2 2 <sup>nd</sup> Edition Rev Dec 19, 2011 FCC Part 15 Class B AS/NZS 60950.1:2011 Inc A1 AS/NZS CISPR 22: 2009+A1:2010 EN 60950-1:2006+A11:2009+A1:2010+A12:2011 EN 55022:2010 EN 61000-3-2:2006+A1:2009+A2:2009 EN 61000-3-3:2008 EN 55024:2010